

LE Series

ELECTRIC SCISSOR LIFTS



**Optional All-Wheel Drive
Provides Superior
Performance
On or Off Slab**



**Automatic Traction Control
and Oscillating Axle for
Rough-Terrain Productivity**



**QuikCharge GenSet Option
Provides Automatic Charging
for Continuous Operation**



**3369LE
4069LE**

www.jlg.com



DIMENSIONAL DATA

A. Platform Height - Elevated:	3369LE	33 ft (10.06 m)
	4069LE	40 ft (12.19 m)
Lowered:	3369LE	5 ft 6.5 in (1.69 m)
	4069LE	5 ft 9 in (1.75 m)
B. Platform Railing Height		3 ft 7.5 in (1.10 m)
C. Overall Height (Rails Up):	3369LE	9 ft (2.74 m)
	4069LE	9 ft 2.5 in (2.81 m)
D. Platform Size		65 x 115 in (1.65 x 2.92 m)
E. Platform Extension		3 ft (.91 m)
F. Overall Width		5 ft 9 in (1.75 m)
G. Overall Length		10 ft 2 in (3.1 m)
H. Wheelbase		7 ft 6.5 in (2.3 m)
I. Ground Clearance		8 in (23 cm)
Platform Capacity:	3369LE	1,000 lb (450 kg)
	4069LE	800 lb (360 kg)
Capacity on Platform Extension		250 lb (113 kg)
Lift/Lower Time:	3369LE	38/42 sec.
	4069LE	54/50 sec.
Maximum Drive Height:	3369LE	Full Height
	4069LE	30 ft (9.14 m)
Gross Vehicle Weight*	3369LE	9,760 lb (4,427 kg)
	4069LE	10,560 lb (4,790 kg)


CHASSIS

Drive Speed	(Lowered)	3.0 mph (4.8 kph)
	(Elevated)	0.4 mph (.64 kph)
Gradeability		35%
Turning Radius (Inside)		90 in (2.3 m)
Tire Size/Type		240/55-17.5 Non-Marking
Brakes		Spring Applied Hydraulically Released Discs

POWER SOURCE

Batteries	8 x 6v 370 Amp-hr
Charger	21 Amp, Automatic SCR Charger
Electric Pump Motor	Series Wound
Drive Motors	Two 5.5 hp Shunt Wound
Pump	Single Section Gear Pump
Hydraulic Reservoir	8.5 gal (32.18 L)
Generator Set	Fully Automatic, 45 Amp Yanmar 6.5 hp Air-Cooled Engine
Engine Fuel Tank	4 gal (15.2 L)

*Certain options or country standards will increase weight.



Standard Features

- 65 x 115 (1.65 x 2.92 m) Work Platform
- Full Time ATC-JLG Automatic Traction Control System
- Oscillating Axle
- Proportional Direct DC Electric Drive
- Proportional Lift Up
- 110V-AC Receptacle in Platform
- 240/55 - 17.5 Foam Filled Non-Marking Tires
- 8 x 6V 370 Amp-Hour Batteries
- 3 ft. Roll Out Deck Extension
- On-Board Diagnostics with Common JLG Analyzer
- Forklift-Able Battery Compartments with Quick Disconnect Couplings
- Fold-Down Hand Rails
- Moveable, Removable Platform Console Box
- 21 Amp Automatic, SCR Battery Charger
- Battery Charge Indicator in Platform
- 3 Degree Tilt Indicator Light and Alarm
- Descent Alarm
- Motion Alarm Programmable with JLG Analyzer
- Manual Descent
- Tie Down Lugs
- Hourmeter
- Horn

Options

- 110V AC Power Pack (Generator)
- All Motion Alarm
- Flashing Amber Beacon
- Hydraulic Leveling Jacks
- Platform Work Lights
- QuikCharge GenSet
- All-Wheel Drive

Versatile Electric Scissor Lifts You Can Take Almost Anywhere!

JLG's Large Electric Series scissor lifts, Models 3369LE and 4069LE, give you the power and versatility to do more on virtually any job site or terrain. With the powerful combination of available all-wheel drive, rugged all-terrain tires, JLG's full-time Automatic Traction Control system, and an oscillating axle, the LE Series provides superior performance where other electric scissor lifts fear to tread, off slab. You can add even more power with options like our hydraulic leveling jacks or the JLG exclusive QuikCharge GenSet automatic charging system for continuous operation and optimum productivity.

Demand the power and versatility you need to get the job done on or off slab. Order an LE Series scissor lift today...and discover the power to do more.

The JLG "1 & 5" Warranty

JLG Industries, Inc. backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable OSHA Regulations in 29 CFR 1910.67, 29 CFR 1926.453, ANSI A92.6-1999, and CSA Standard CAN3-B354.2-M82, as originally manufactured for intended applications.

JLG Industries, Inc.

1 JLG Drive, McConnellsburg, PA 17233-9533
Telephone 717-485-5161 Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

Printed in USA
FORM NO.: SS-LE-902-15M
PART NO.: 3131502
R10022

