SKYJACK SJPI SERIES Industrial Personnel Lift

Low-cost. Reliable. Easy-to-use.

The SJPI Series from Skyjack adds yet another dimension to our full line of personnel lift products. The 15' model and 20' NS model require no outriggers or stabilizers for operation. Simply position the unit in the desired work location and secure the unit in place with the floor locking device. Short, built-in stabilizers on the 20', 25' and 30' models swing-out for quick and easy setup. Set stabilizers in place and depress the floor lock with your foot and these models are ready to use! It's easy to store and compact enough to fit easily into corners and confined spaces. It's suitable for a variety of industrial and maintenance applications in hospitals, government facilities, schools, warehouses, churches and shopping malls. The SJPI personnel lift from Skyjack can help meet your needs at a price you can afford!


Standard features include:

- Working heights from 21 ft. to 31 ft.
- ▶ Two-handed, pushbutton operator controls
- "Clamshell" platform with low entry and interlock system
- ▶ Indicator lights on stabilizers (20', 25', and 30')
- ▶ 110V GFI AC outlet on platform
- Emergency lowering from base
- Compact design all models can pass thru a standard 6'8" doorway
- Heavy duty aluminum mast sections provide strength and rigidity
- AC units available with 110V or 220V power source
- ▶ Rugged steel base provides maximum stability
- Tiedowns and forklift pockets
- Non-marking wheels and casters
- Comprehensive Operation, Parts & Service Manual
- ANSI compliance



Shown: Model SJPI 20' with "clamshell" platform and optional DC power package

SKYJACK SJPI SER



Built-in stabilizers on 20', 25', and 30' models swing-out for quick and easy set-up.



Foot-activated floor locking device helps keep unit securely in place.



Two-handed, pushbutton operators control console keeps both hands inside platform.



Optional DC power. Steel cover protects battery and charger - opens wide for easy access.



"Clamshell" platform with interlock prevents lift if guardrail is not closed. Also prevents guardrails from opening when elevated.



15' model requires no stabilizers! Floor locking device secures unit in place for operation.

Spec	ificat	ions:	SJPI	Serie	S						
Model	Work Height (Nom.)	Raised Height (Nom.)	Lowered Platform Height	O/A Width	O/A Length	Stowed Height	Capacity Lbs. (kg)	Platform Size	AC Power	Stabilizer Footprint	Weight Lbs.‡ (kg)
SJPI 15'	21' (6.4m)	15' (4.6m)	15" (0.38m)	29.5" (0.75m)	57.5" (1.46m)	79" (2.01m)	350 (159kg)	24" x 28" (.61x.71m)	110V or 220V	NONE	850 (386kg)
SJPI 20'	26' (7.9m)	20' (6.1m)	15" (0.38m)	29.5" (0.75m)	57.5" (1.46m)	79" (2.01m)	350 (159kg)	24" x 28" (.61x.71m)	110V or 220V	50" (1.27m)	920 (417kg)
SJPI 20' NS†	26' (7.9m)	20' (6.1m)	15" (0.38m)	29.5" (0.75m)	57.5" (1.46m)	79" (2.01m)	350 (159kg)	24" x 28" (.61x.71m)	110V or 220V	NONE	1100 (499kg)
SJPI 25'	31' (9.4m)	25' (7.6m)	15" (0.38m)	29.5" (0.75m)	64" (1.63m)	79" (2.01m)	350 (159kg)	24" x 28" (.61x.71m)	110V or 220V	50" (1.27m)	1080 (490kg)
SJPI 30'	36' (11m)	30' (9.1m)	15" (0.38m)	29.5" (0.75m)	64" (1.63m)	79" (2.01m)	350 (159kg)	24" x 28" (.61x.71m)	110V or 220V	56.5" (1.44m)	1490 (676kg)
‡Standard weight on AC models. Add 80# for DC models.										NS=No Stabilizers	

\$\pmax\$Standard weight on AC models. Add 80\pmax for DC models. **Optional Equipment:**

- DC Power Package
- Tool Tray
- Stabilizer packages available for other countries
- Box Cage Narrow Platform
- Fluorescent Tube Caddy
- Emergency Battery Back-up (AC units)

This literature for illustrative purposes only. Consult Parts/Operating and Service Manual for proper operating and maintenance procedures. Work platforms have been tested to comply with applicable standards as interpreted by Skyjack, Inc. Specifications are subject to change without notice.

Distributed By:



SKYJACK SKYJACK, MFG.

Hwy. 4 South, P.O. Box 249, Emmetsburg, IA 50536 Phone: (712)852-4294 • (888)SJPLIFT Fax: (888)283-1913

SKYJACK CORP. (USA)

3451 Swenson Ave., St. Charles, IL 60174 Phone: (630)262-0005 • (800)2SKYJACK FAX: (630)262-0006

FORM SJPI 7/96 Printed in USA